

### DESCRIPTION

<b>CATALOG:</b> E-724-U-226-M1-S	<b>BALLAST TYPE:</b> Electronic	<b>STARTING METHOD:</b> Programmed Rapid Start	<b>NUMBER OF LAMPS - LAMP TYPE:</b> (2) F26W, (1) F26W, (1) F42W, (1) F32W Triple or Quad T4, (2) F24/27W Long Twin Tube T5, (2) F21, (1) F28, (1) F38W 2D T5 (1) FC9 22W, (1) FC12 40W Circline T5
-------------------------------------	------------------------------------	---	---

### ELECTRICAL CHARACTERISTICS

<b>INPUT VOLTAGE:</b> 120 – 277 V~ +/- 10%	<b>LAMP WATTS:</b> 26/42/32/24/21 28/38/22/40W	<b>INPUT WATTS:</b> 25 to 55 W	<b>INPUT CURRENT:</b> 0,255 – 0,55 A	<b>OCV:</b> 425 V~ Min	<b>PF:</b> > 0,98	<b>FREQUENCY:</b> 50 / 60 Hz	<b>SOUND RATED:</b> A
<b>MIN START TEMP:</b> 32°F / 0°C	<b>CLASS:</b> P	<b>TYPE:</b> 1 outdoor	<b>BALLAST FACTOR:</b> 85%	<b>BEF:</b> 1.54	<b>LAMP CONNECTION:</b> Series	<b>THD (1):</b> < 10 %	<b>NO PCB'S</b>

(1) FOR 2-F26T4

### PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS						
	UNITS	M1	M2	M3	W	L	H
	INCHES TOL(+/-)	N/A	N/A	4,185 0,0125	2,425 0,0125	4,925 0,0125	1,050 0,0125
	MM TOL(+/-)	N/A	N/A	106,29 0,317	61,59 0,317	125,09 0,317	26,67 0,317
	LEAD LENGTH						
UNITS	BLACK	WHITE	RED	BLUE	BLUE		
INCHES TOL(+/-)	N/A	N/A	N/A	N/A	N/A		
MM TOL(+/-)	N/A	N/A	N/A	N/A	N/A		

### CARTON CHARACTERISTICS

<b>UNITS/CARTON</b> 10	<b>CARTONS/LAYER</b> 22	<b># OF LAYERS</b> 10	<b>UNITS/PALLET</b> 2200	<b>PIECE WEIGHT</b> 0,41lb	<b>CARTON WEIGHT</b> 4.38 lb	<b>PALLET WEIGHT</b> 1014 lb
<b>CARTONS/PALLET</b> 220	<b>CARTON DIMENSIONS</b> 5.31" x 13.58" x 2.55"		<b>PALLET DIMENSIONS</b> 40" x 48" x 5.9"		<b>PALLET DIMENSIONS LOADED, INCLUDING WOOD PALLET</b> 40"X48"X 35.43"	


### MISC.

--

#### CARTON LABEL

#### PRODUCT LABEL

#### ELECTRICAL DIAGRAM



### ISB LIGHTING & POWER SOURCE

2840 KELLER SPRINGS ROAD,  
SUITES 1102 AND 1103  
CARROLLTON, TX. 75006  
U.S.A.  
Tel. 972-416-4500  
Fax. 972-418-5858

Data is based upon tests performed by Industrias Sola Basic in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

Made in Mexico by Industrias Sola Basic S.A. de C.V.