


CATALOG NUMBER: E-MCA0FT201F FOR ONE 200 WATT, M136 METAL HALIDE PULSE START LAMP

Line Voltage	120/277V
Regulation	
Line Volts	+/- 10%
Lamp Watts	+/-10%
Frequency	60 Hz
Circuit Type	CWA
Power Factor (min)	90%
Insulation Class	A(105°)
Min. Ambient Starting Temp.	-20° F or -30° C




Line Voltage (Volts)	120	277
Line Current (Amps)		
Operating	2.05	0.90
Open Circuit	2.05	0.90
Starting	1.35	0.58
Input Watts (W)	240	240
Open Circuit Voltage (V)	280	280
Drop Out Voltage (V)	60	138
UL(1029) Bench Top Rise		
Recommended Fuse (Amps)	6	3
HIGH POTENTIAL TEST (VOLTS)		
1 Minute	2000	
2 Seconds	2500	
Open Circuit Voltage Test(volts)	254-310	
Short-Circuit Current Test (Amps)		
Secondary Current	1.7 - 2.0	
Input Current (Amps)	1.05 - 1.45	0.40 - 0.65

Weight (Lbs)	13.00
Lead lengths (Inches)	12.00
Sound rating	B

IGNITOR: IN CAN

The ignitor is included as part of the potted assembly.
Ballast to Lamp distance (BTL)= 50 feet.
Temp. Rating: 90° C

WIRING DIAGRAM



120/277 VOLT CONNECTION

ISO 9001:2000



Data is based upon tests performed by Industrias Sola Basic in a controlled environment and representative of relative performance. Actual Performance can vary depending on operating conditions. Specifications are subject to change without notice.