

ISB SOLA BASIC



REV: "A"

FLUORESCENT BALLAST SPECIFICATIONS

DESCRIPTION

CATALOG E450-T-260 IC	TYPE Energy efficient magnetic	STARTING METHOD Instant Start	NUMBER OF LAMPS 2	LAMP TYPE F96SST12, F96T12, F72T12
---------------------------------	-----------------------------------	----------------------------------	----------------------	---------------------------------------

ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE 277v	LAMP WATTS 60/75/55w	INPUT WATTS 162w	INPUT CURRENT 0.60 A	OCV 690v	PF 0.97	FREQUENCY 60 Hz	SOUND RATED B
MIN START TEMP 50°F (60°F/SS lamp)	CLASS P	TYPE 1 outdoor	BALLAST FACTOR 0.93 (0.93 / SS lamp)	BEF 0.574	THD 25%	NO PCB'S	

PHYSICAL CHARACTERISTICS


	CASE DIMENSIONS						
	UNITS	M1	M2	M3	W	L	H
	INCHES	2.0	11.140	10.5	3.109	11.750	1.781
	TOL(+/-)	0.010	0.010	0.010	0.050	0.050	0.050
	MM	51	283	267	79	298	45
	TOL(+/-)	0.25	0.25	0.25	1.30	1.30	1.30
LEAD LENGTH							
UNITS	BLACK	WHITE	RED	BLUE	YELLOW		
INCHES	8	62	46	46	62		
TOL(+/-)	3/8	3/8	3/8	3/8	3/8		
MM	203	1574	1168	1168	1574		
TOL(+/-)	10	10	10	10	10		

CARTON CHARACTERISTICS

UNITS/CARTON 6	CARTONS/LAYER 12	# OF LAYERS 4	UNITS/PALLET 288	PIECE WEIGHT 8 lbs	CARTON WEIGHT 49 lbs	PALLET WEIGHT 2,391 lbs
CARTONS/PALLET 48	CARTON DIMENSIONS 12" x 12" x 4"		PALLET DIMENSIONS 40" x 48" x 7"	PALLET DIMENSIONS LOADED, INCLUDING WOOD PALLET 40" x 48" x 24"		

CARTON LABEL

ELECTRICAL DIAGRAM



PRODUCT LABEL

<p>SOLA</p>				
<p>277 VOLT 0.60 AMP 690 OCV 60 HZ</p> <p>FOR: 2 F96T12/IS or 2 F72T12/IS or at 15.5° C Min. amb. 2-F96T12/IS/ES</p> <p>< 600 Volts to Ground</p> <p>SOUND RATED B</p> <p>3 YEAR WARRANTY</p>	<p>HIGH POWER FACTOR INSTANT START BALLAST</p> <p>E450-T-260 IC</p> <p>MINIMUM 10° C MADE IN MEXICO</p> <p>TYPE 1 OUTDOOR CLASS P NON PCB</p>			

Lighting and Power Source
2707 Realty Road, Suite 110
Carrollton, TX 75006
Tel: (888) 385-4448
Fax: (972) 418-5858